

## Řezače trubek

Running Diameter	1-5/32" (GOEX)	1.230"	1.230 (GOEX)	1.390"
Temperature Rating (F)	400 - 500	400 - 500	400 - 500	400 - 500
Pressure Rating (PSI)	15,000	12,000	15,000	15,000
Explosive Weight (g)	7.0	14.0	7.0	18.0
Recommended Application	1.66" Tubing, 2.4#	1.66" Tubing, 2.4#	1.66" Tubing, 2.4#	1.90" Tubing, 2.9#

Running Diameter	1.390" (GOEX)	1.460" (GOEX)	1.560"	1.560" (GOEX)
Temperature Rating (F)	400 - 500	400 - 500	400 - 500	400 - 500
Pressure Rating (PSI)	15,000	15,000	15,000	15,000
Explosive Weight (g)	9.0	20.0	11.0	14.0
Recommended Application	1.90" Tubing, 2.90#	2-1/16" Tubing, 3.25#	2-1/16" Tubing, 3.25#	2 3/8" Tubing, 4.85 & 6.65#

Running Diameter	1 11/16"	1 11/16" (GOEX)	1 3/4"	1 3/4" (GOEX)
Temperature Rating (F)	400 - 500	400 - 500	400 - 500	400 - 500
Pressure Rating (PSI)	15,000	15,000	15,000	15,000
Explosive Weight (g)	13.0	21.0	13.0	18.0
Recommended Application	2-3/8" Tubing, 4.7#	2-3/8" Tubing, 4.85 & 6.65#	2-3/8" Tubing, 4.7#	2-3/8" Tubing, 4.85 & 6.65#

Running Diameter	1 13/16"	1 13/16" (GOEX)	2 1/16"	2 1/16" (GOEX)
Temperature Rating (F)	400 - 500	400 - 500	400 - 500	400 - 500
Pressure Rating (PSI)	15,000	15,000	15,000	15,000
Explosive Weight (g)	13.0	18.0	22.7	22.7
Recommended Application	2-3/8" Tubing, 4.7#	2-3/8" Tubing, 4.85 & 6.65#	2-7/8" Tubing, 8.7#	2-7/8" Tubing, 6.85#

Running Diameter	2 1/8"	2 1/8" (GOEX)	2-1/4"	2-1/4" (GOEX)
Temperature Rating (F)	400 - 500	400 - 500	400 - 500	400 - 500
Pressure Rating (PSI)	15,000	15,000	15,000	15,000
Explosive Weight (g)	18.0	22.7	18.0	22.7
Recommended Application	2-7/8" Tubing, 6.5#	2-7/8" Tubing, 6.85#	2-7/8" Tubing, 6.5#	2-7/8" Tubing, 6.85#

